

INVERTER GENERATORS

from 0,8 kW to 3,1 kW



Stable output power with low consumption and noise exposure!



Easy to handle and maintain, GS and CE certified. (pic left: PG 950i and PG 1200i)

The low sound pressure and high performance makes the PG-generators the ideal power producers for leisure and worksite..



Model	PG 950i	PG 1200i	PG 2000i	PG 2600i	PG 3100i
Frequency	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
Max. Output AC	800 W	1.200 W	2.000 W	2.600 W	3.000 W
Nominal power AC	700 W	1.000 W	1.700 W	2.300 W	2.800 W
Nominal voltage AC	230V	1 x 230 V	2 x 230 V	2 x 230 V	2 x 230 V
Cubic capacity	40 ccm	60 ccm	99 ccm	125ccm	149,5 ccm
Fuel			lead-free petrol		
Tank capacity	2,1 l	3,0l	4,1 l	7,5l	7,5l
Nonstop operating hours	4,1 h	4 h 48 min	3 h 48 min	5 h 10 min	4 h 10 min
Sound pressure (in 7 m)	58 db	58 db	58 db	62 db	62 db
Size (L x W x H) in mm	425x230x380	448x236x392	525x282x457	614x341x506	614x341x506
Weight	8,5 kg	12,1 kg	18,5 kg	33 kg	33 kg

POWERTOOL
by javac-deutschland.de

Javac Deutschland GmbH
Industriestraße 29/2
D-73340 Amstetten

Tel. +49(0)7331-3 05 80
Fax +49(0)7331-30 58 58

www.javac-deutschland.de
info@javac-deutschland.de