

# Turnrollers

## Roller block HGZT with 2 AC-Motors to 150 t

### Self-centring

The HGZT series has two synchronously operating drive units that provide continuous rotation with infinitely variable speed control. The roller spacing is self-centring and the rollers align with the diameter of the workpiece.



### Features

- For turning and positioning workpieces in the sections of mechanical engineering, container building, plant construction and pipeline construction.
- With 2 AC motors
- Self centring wheel distance
- Automatic adaptation to the workpiece for different diameters
- With two synchronous driven motors.
- Adjustable rotating speed.
- PU-Rolls.
- Remote control

Scope of delivery:  
1 Remote control

Model	Speed	Max. Load	Workpiece diameter	Motor (Kw) Power	rubber diameter	rubber rollers width	Item no.
HGZT-5	6 - 60 m/h	5.000 kg	250 - 2.500 mm	2x0,37	250 mm	100 mm	02.20.10.20150
HGZT-10		10.000 kg	320 - 3.200 mm	2x0,55	300 mm	120 mm	02.20.10.20100
HGZT-20		20.000 kg	500 - 3.800 mm	2x1,1	350 mm	150 mm	02.20.10.20200
HGZT-40		40.000 kg	600 - 4.500 mm	2x1,5	400 mm	160 mm	02.20.10.20400
HGZT-60		60.000 kg	750 - 5.000 mm	2x2,2	450 mm	180 mm	02.20.10.20600
HGZT-80		80.000 kg	850 - 5.500 mm	2x3	450 mm	240 mm	02.20.10.20800
HGZT-100		100.000 kg	1.000 - 6.300 mm	2x3	500 mm	240 mm	02.20.10.21000
HGZT-150		150.000 kg	1.000 - 6.300 mm	2x4	500 mm	300 mm	