

NEW IN OUR PRODUCT RANGE

until revocation

AVALON 65 CNC

Cutting - cleanly and reliably

AVALON 65 CNC is a lightweight handy plasma cutting unit with high cutting performance and an excellent cutting quality. Their low weight makes them ideal devices for trade, shop and industry For the use as CNC-Plasma Cutting the Avlon 65 CNC is provided with a specific point of intersection.

Feature

- IGBT technology
- Microprocessor control system for superior & dynamic arc characteristics
- CNC interface connection
- Non HF arc starting system for increased reliability and low EMF pollution
- Air flow manual activation switch to set test air pressure, pressure without the need to trigger the torch.
- Intelligent protection sys tem protects plasma torchfrom damage incorrect air pressure, consum bles not in place, excessive pilot arc use

Model		AVALON 65 CNC
Supply voltage(V)		3-380/V 400V ±10% /50/60Hz
Rated input current		18 A
Rated input power		7,8 KW
Current adjustment range		20 A ~ 65 A
No-load voltage		450 V
Duty cycle 40°C 10 min		90% 65A 100% 61A
Piercing on CNC machine max.		≤12 mm
The max. cutting thickness to Carbon steel		≤35 mm
Optimal cutting thickness *	Carbon steel	≤25 mm
	Stainless steel	≤25 mm
	Aluminum	≤20 mm
	Copper	≤14 mm
Measuremt (LxWxH) mm		663x253x423
Protection class		IP23
Insulation class		Н
Weight		24 kg
Cooling		AF
Item no.		02.02.10.00061
dications for hand tor	ch	











Avalon 65 CNC

Scope of delivery:

1 Earth cable 3 m

Optional

Hand torch PT-60/6m Price: 335,-€

Optional for CNC use

Machine torch PTM-60 with coaxialcable /6 m

Price: 450,- € Machine torch

PTM-60 with coaxialcable

/12 m

Price: 540,- €

*Indications for hand torch

Subject to misprints, errors and technical changes! 08.01.2025

For more info click on us:

http://www.javac.org → Current Offers

Industriestraße 29/2 D-73340 Amstetten

Tel. +49 (0)7331-30580 Fax +49 (0)7331-305858 **Order Processing** +49(0)7331 - 305820 **Technical information** +49(0)7331 - 305824

SPECIALIST SHOP

