

Profi-Line Plasma

CNC Plasma Cutting

Optional Air dusting table or water table for CNC Plasma Cutting

We provide customers with two types of high-efficiency dust-removing load-bearing tables.

Option 1: Water table absorbs metal residues through water, effectively reducing dust..

Option 2: Air dusting table the load-bearing table and dust collector are connected through an additional down-fl ow system to achieve a perfect dust removal effect.



Air dusting table
1.500 x 3.000 mm
max. Workpiece
thickness 30 mm

Water table / Air dusting	1.300 x 1.300 mm	1.300 x 3.000 mm
max. Workpiece thickness	0,5 mm - 30 mm	0,5 mm - 30 mm
Needed external dust collector	≥ 5.5 kw	≥ 5.5 kw
with Segment extraction table	without	only with (item 02.02.53.01530)
Item no.	02.02.52.01315	—

Productvideo



CNC plasma tube machine

CNC Tube S2

The CNC Tube S2 is a cost-effective tube cutting solution designed on a compact platform. The Tube S2 is ideal for roll cage, railing and fencing manufacturers, as well as many other small to medium sized manufacturing operations looking to increase efficiency in profiling and cutting their workpieces. This 2-axis CNC tube cutting machine can cut aluminium, stainless steel and mild steel tubes quickly and easily



Model	CNC Tube S, 2-Axis
Power	110V / 220V, 1-phase / 60Hz
Running speed	0-8,000mm/min
Pipe Capacity	30 - 120 mm
Height control	HYD Arc voltage THC
Travel in longitudinal direction	3m / 6m / 9m / 12m / 15m (Extension by 3 metres)
Max. Cutting speed	0 - 8000mm/min.
Rotation drive	Precision planetary gear and belt drive
Linear movement	Precision rod and gear
Cutting process	Plasma

Optional:
- Libellula® TUBE 2-axis software
with nesting function

Control with
USB interface



Productvideo

*All CNC plasma systems are delivered without oxyfuel equipment!