Turnrollers

Support Block TR-1000 kg

Useful and versatile

With Turnrollers of the TR series, it is very easy to position containers and pipes with a diameter of 80 mm to 700 mm and to weld circumferential seams. Due to the low initial costs, the purchase pays for itself in a very short time. With the help of a torch stand, the welding process can be further simplified and the welder can concentrate exclusively on controlling the welding process.

Features

- Device for the turning and positioning of small tanks and cylindrical workpieces.
- Equipped with high performance PU coated metal roller to provide stable running
- DC infinitely variable speed control system (TR-1000)
- AC variable speed control system (TR-2000)
- Switch for cw/ ccw rotation, foot switch for start/stop functions.
- High frequency protection

Model	TR-1000 complete
Max Load	1000kg
Pipe Diameter Range	Ø 80-700mm
Rotation Speed	80 - 1600mm/min
Rotation Power	DC 0,12 kW
Roller Size	Ø250x50mm
Roller Material	Steel coated with PU
Measurement (LxWxH) mm	500x300x384mm (Driver) 500x160x384mm (Idler)
Weight (complete)	85 kg
Item no.	02.30.10.20100



nitial ne. With e further ly on pic. TR-1000

Scope of delivery TR-1000:

- 1 Drive unit with control (integrated)
- 1 Idler
- 1 Foot switch

Optional:

1 Idler

Modell	TR-1000 Idler
Load	500 kg
Workpiece Diameter	Ø 80-700mm
Weight	33 kg
Measurement $(LxWxH)$	500x160x384mm
Item no.	02.30.10.20102